



FEATURES

- Excellent linearity
- Extremely low noise
- High gain
- Excellent return loss properties

APPLICATIONS


- Single module line extender in CATV systems operating in the 40 to 860 MHz frequency range.

DESCRIPTION

Hybrid high dynamic range amplifier module operating at a supply voltage of 24 V (DC) in a SOT115J package. The Module consists of two cascaded stages both in cascode configuration.

PINNING - SOT115U

PIN	DESCRIPTION
1	input
2	common
3	common
5	+VB
7	common
8	common
9	output



Side view

Fig.1 Simplified outline

QUICK REFERENCE DATA

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
G _p	power gain	f=50MHz	33.5	35	dB
		f=750MHz	35	-	dB
I _{tot}	total current consumption (DC)	V _B =24V	290	320	mA

LIMITING VALUES

In accordance with the Absolute Maximum Rating System (IEC 134).

SYMBOL	PARAMETER	MIN.	MAX.	UNIT
V_B	supply voltage	-	25	V
V_i	RF input voltage	-	55	dBmV
T_{stg}	storage temperature	-40	+100	
T_{mb}	mounting base operating temperature	-20	+100	

 **CHARACTERISTICS**

Bandwidth 40 to 860 MHz; $V_B=24V$; $T_{case}=30^{\circ}C$; $Z_s=Z_L=75\Omega$

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
G_p	power gain	f=50MHz	33.5	35	dB
		f=860MHz	35	-	dB
SL	slope cable equivalent	f=40 to 860 MHz	0.5	3.0	dB
FL	flatness of frequency response	f=40 to 860 MHz	-	± 0.5	dB
S_{11}	input return losses	f=40 to 80 MHz	20	-	dB
		f=80 to 160 MHz	20	-	dB
		f=160 to 320 MHz	20	-	dB
		f=320 to 640 MHz	18	-	dB
		f=640 to 860 MHz	18	-	dB
S_{22}	output return losses	f=40 to 80 MHz	20	-	dB
		f=80 to 160 MHz	18.5	-	dB
		f=160 to 320 MHz	17	-	dB
		f=320 to 640 MHz	17	-	dB
		f=640 to 750 MHz	16	-	dB
CTB	composite triple beat	84 channels flat; $V_o=44dBmV$; measured at 543.25 MHz	-	-60	dB
X_{mod}	cross modulation	84 channels flat; $V_o=44dBmV$; measured at 49.725 MHz	-	-64	dB
CSO	composite second order distortion	84 channels flat; $V_o=44dBmV$; measured at 544.5 MHz	-	-68	dB
d_2	second order distortion	Note1	-	-64	dB
V_o	output voltage	Dim= -60 dB; note 2	59	-	dBmV
F	noise figure	f=860MHZ	-	6	dB
I_{tot}	total current consumption (DC)	Note 3	290	320	mA

Note :

1. $f_p=49.75\text{MHz}$; $V_p=44\text{dBmV}$;
 $f_q=807.25\text{MHz}$; $V_q=44\text{dBmV}$;
measured at $f_p+f_q=857\text{MHz}$.
2. Measured according to DIN45004B;
 $f_p=847.25\text{MHz}$; $V_p=V_o$;
 $f_q=855.25\text{MHz}$; $V_q=V_o-6\text{dB}$;
 $f_r=857.25\text{MHz}$; $V_r=V_o-6\text{dB}$;
measured at $f_p+f_r-f_q=849.25\text{MHz}$.
3. The module normally operates at $V_B=24\text{V}$, but is able to withstand supply transients up to 28 V.

 **PACKAGE OUTLINE**

Rectangular single-ended package; aluminum flange; 2 vertical mounting holes; 2×6-32 UNC AND 2 extra horizontal mounting holes; 7 gold-plated in-line leads

