



FEATURES

- Excellent linearity
- Extremely low noise
- Excellent return loss properties

APPLICATIONS


- Single module line extender in CATV systems operating in the 5 to 200 MHz frequency range.

DESCRIPTION

Hybrid high dynamic range amplifier module operating at a supply voltage of 24 V (DC) in a SOT115J package. The Module consists of two cascaded stages both in cascode Configuration.

PINNING - SOT115U

PIN	DESCRIPTION
1	input
2	common
3	common
5	+VB
7	common
8	common
9	output



Side view

Fig.1 Simplified outline

QUICK REFERENCE DATA

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
G _p	power gain	f=10MHz	23.5	24.9	dB
I _{tot}	total current consumption (DC)	V _B =24V	145	195	mA

LIMITING VALUES

In accordance with the Absolute Maximum Rating System (IEC 134).

SYMBOL	PARAMETER	MIN.	MAX.	UNIT
V _B	supply voltage	-	25	V
V _i	RF input voltage	-	55	dBmV
T _{stg}	storage temperature	-20	+100	
T _{mb}	mounting base operating temperature	-20	+100	



CHARACTERISTICS

Bandwidth 5 to 200 MHz; V_B=24V; T_{case}=30°C ; Z_s=Z_L=75Ω

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
G _p	power gain	f=10MHz	23.5	24.9	dB
SL	slope cable equivalent	f=5 to 200 MHz	-0.2	1.0	dB
FL	flatness of frequency response	f=5 to 200 MHz	-	±0.35	dB
S ₁₁	input return losses	f=5 to 200 MHz	18	-	dB
S ₂₂	output return losses	f=5 to 200 MHz	16	-	dB
CTB	composite triple beat	17 channels flat; Vo=50dBmV; measured at 200.25 MHz	-	-61	dB
X _{mod}	cross modulation	17 channels flat; Vo=50dBmV; measured at 49.75 MHz	-	-65	dB
CSO	composite second order distortion	17 channels flat; Vo=50dBmV; measured at 201.25 MHz	-	-65	dB
Vo	output voltage	Dim= -60 dB; note 1	60	-	dBmV
F	noise figure	f=200MHz	-	5.5	dB
I _{tot}	total current consumption (DC)	Note 2	145	195	mA

Note :

1. Measured according to DIN45004B;

f_p=184.25MHz; V_p=V_o;

f_q=192.25MHz; V_q=V_o-6dB;

f_r=194.25MHz; V_r=V_o-6dB;

measured at f_p+f_r-f_q=186.25MHz.

2. The module normally operates at V_B=24V, but is able to withstand supply transients up to 28 V.



PACKAGE OUTLINE

Rectangular single-ended package; aluminum flange; 2 vertical mounting holes;
2×6-32 UNC AND 2 extra horizontal mounting holes; 7 gold-plated in-line leads

